



Mast Amplifiers



Range: TVF-230/250



NEW

OPTION

Rejection

5G

READY

107

dBμV

IP23

Power supply

24V

Rejection

4G

lte



114x110x41mm



Option in Kit's

- KIT-531 = TVF-231 + AF-24V
- KIT-532 = TVF-232 + AF-24V
- KIT-533 = TVF-233 + AF-24V
- KIT-534 = TVF-234 + AF-24V
- KIT-535 = TVF-235 + AF-24V



For amplifiers with channel 21-69(UHF) add the letter Z to the ref.

REF.	TVF-232	TVF-233	TVF-234	TVF-235	TVF-251UL	TVF-252UL	TVF-252/FM	
INPUTS	2 BI/BIII UHF	3 BI/BIII UHF1 UHF2	1 UHF	2 UHF1 UHF2	1 UHF	2 UHF1 UHF2	2 FM UHF	
GAIN	dB	BI/BIII: 30 UHF: 36		UHF: 36		UHF: 40	UHF: 40	FM: 15 UHF: 40
ADJUSTABLE GAIN RANGE	dB	20						
MAXIMUM OUTPUT LEVEL	dBμV	107* 104**						
SUPPLY	VDC	24						
CONSUMPTION	mA	40						
NOISE FIGURE	dB	UHF: 3,5						
CONNECTION	«F» Connectors							

*DIN 45004B, IMD3= -60dB, 3P

**EN 50083-3, IMD3= -60dB, 2P