

MegaLine[®] F10-130 S/F Dca

KS-02YSCH 4 x 2 x AWG 22/1 PIMF



 Category 7_A **S₃ P₄ A₄ C₅ E₅**


Illustration similar

Construction

Conductor bare copper wire, AWG 22/1
 Insulation cellular-PE, core-Ø: nominal value 1.6 mm
 Colour code wh/bl, wh/or, wh/gn, wh/br
 Element cores to pair
 Pair shielding aluminium-bonded polyester tape


Twisting PiMF to cable core
 Outer sheath Halogen free flame retardant compound (LS0H)
 material
 Colour Colza yellow

Cable marking

KERPEN DATACOM Made in Germany MegaLine F10-130 S/F 4P H Cat.7A 25G 4PPoE Dca s2 d2 a1 DoP: CDESK0000007 \$BA-Nr.\$ \$m-sign.\$

Fire Behaviour

Fire class / DoP Dca -s2,d2,a1 / CDESK0000007
 Fire performance EN 50575 / EN 50399
 Flame retardancy acc. to IEC 60332-3-24
 Halogen-free IEC 60754-1/2
 Acidity IEC 60754-2
 Smoke density IEC 61034-2
 Fire load (approx.) 0.7 MJ/m



Security (fire behaviour)

Performance


better than Category 7 acc. to EN 50288 and IEC 61156
 excellent NEXT, low attenuation, exzellente screen properties
 (pair- and overall screen), low Skew
 Transmission bandwidth (typ.) 1300 MHz



Performance (class, bandwidth)

Applications


Installation cable for generic cabling systems acc. to ISO/IEC 11801 and EN 50173 (3rd edition). Ideal for all applications of class D up to FA Multimedia (Video, Data, Voice) >10 GbE acc. to IEEE 802.3 an, Cable sharing, VoIP, PoE/PoE+/4PPoE



Application (Ethernet, TV)

Mechanical characteristics (cable)


Bending radius (static) (min.) 4x outer-Ø
 Bending radius (dynamic) (min.) 8x outer-Ø
 Max. strain relief 130 N
 Crush resistance (long term) 1000 N/100mm
 Impact strength (quantity of impacts) 10



Construction (conductor size, tensile strength)

Electromagnetic behaviour

Coupling resistance @ 10 MHz (nom.) 5 mΩ/m
 Screen attenuation (nom.) 70 dB
 Coupling attenuation (nom.) 85 dB
 Segregation class according to EN 50174-2 d



EMC (coupling attenuation)

MegaLine® F10-130 S/F Dca

KS-02YSCH 4 x 2 x AWG 22/1 PIMF

 Category 7_A **S₃ P₄ A₄ C₅ E₅**
Electrical properties at 20°C

DC resistance (max.)	57.1 Ω/km
Insulation resistance (min.)	5 GΩ x km
Operating capacity (approx.)	40 pF/m
Capacitive coupling (e) (approx.)	1100 pF/km
Signal velocity (approx.)	0.77 x c
Phase delay	420 ns/100m
Skew @ 100 MHz (approx.)	5 ns/100m
Characteristic impedance @ 100 MHz	100 +/- 5 Ω
Test voltage	1000 V
Operating voltage (max.)	125 V

Thermal characteristics (cable)

Temperature (transport / storage)	-20 °C up to +60 °C
Temperature during installation	0 °C up to +50 °C
Temperature after installation	-20 °C up to +60 °C

Frequency MHz	Attenuation dB/100m		NEXT dB		PSNEXT dB		ACR-N dB@100m		PSACR-N dB@100m		ACR-F dB@100m		PSACR-F dB@100m		RL dB	
	typ.	Cat.7 _A max.*	typ.	Cat.7 _A min.*	typ.	Cat.7 _A min.*	typ.	Cat.7 _A min.*	typ.	Cat.7 _A min.*	typ.	Cat.7 _A min.*	typ.	Cat.7 _A min.*	typ.	Cat.7 _A min.*
1	1,7	2,1	105	78	102	75	104	75,9	101	72,9	105	78	102	75	27,1	-
10	4,5	5,8	105	78	102	75	101	72,2	98	69,2	108	78	105	75	35,2	25,0
100	15,4	18,5	105	75	102	72	90	56,9	87	53,9	93	65	90	62	38,9	20,1
200	22,9	26,5	105	71	102	68	83	44,4	80	41,4	85	59	82	56	36,6	18,0
250	26,0	29,7	105	69	102	66	79	39,7	76	36,7	82	57	79	54	35,3	17,3
500	35,9	42,8	100	65	97	62	64	22,1	61	19,1	70	51	67	48	29,4	17,3
600	40,4	47,1	95	64	92	61	55	16,6	52	13,6	63	50	60	47	26,6	17,3
700	44,6	51,1	95	63	92	60	50	11,6	47	8,6	60	48	57	45	25,8	16,6
800	47,7	54,9	93	62	90	59	45	7,0	42	4,0	57	47	54	44	25,0	16,1
900	51,6	58,5	90	61	87	58	38	2,6	35	-0,4	53	46	50	43	23,6	15,5
1000	54,8	61,9	88	60	85	57	33	-1,5	30	-4,5	48	45	45	42	22,3	15,1
1100	56,9	-	87	-	84	-	30	-	27	-	44	-	41	-	21,4	-
1300	61,4	-	80	-	77	-	21	-	18	-	39	-	36	-	18,3	-

* EN 50288-9-1(2013) / IEC 61156-5(2020)

Standards, certificates and approvals

Conformity

 to CPR (EU/305/2011)
 acc. to LVD (2014/35/EU)

Quality seal with production control

GHMT PVP

Link Performance

KERPEN DATACOM MegaLine® systems and further commercial plug-in connector

Part number	Weight	copper weight	Outer Ø approx.	Colour
LKD7KS700010100	76 kg/km	45 kg/km	8.4 mm	Colza yellow