

GigaLine[®] U-DQ(ZN)BH - B2ca

universal cable, stranded loose tube

E9/125 OS2



Illustration similar

Description

Fibre optic universal cable, multi tube, longitudinally watertight, with non-metallic rodent protection.

Properties / applications

Universal cable for fixed installation. Not suitable for underground laying (direct buried).

For use in highly sensitive buildings with very high fire protection requirements such as escape routes in care and support facilities, hospitals, etc. Suitable for campus/ backbone cabling and for the use in generic cabling acc. to ISO/IEC 11801 and EN 50173. Especially suitable for mounting of distribution heads für pre-assembled trunks and for splicing technology. Building entries without additional transition points (splices) possible.

Laying

Indoor and outdoor installation in dry conduits, on covered cable trays. For automated cable pulling with cable winches the use of tensile-force-recording equipment is obligatory.

Construction

Product name	GigaLine [®] U-DQ(ZN)BH - B2ca
Fibre quality	E9/125 0,36F3/0,22H18-SMF28 ultra OS2
Fiber colours	IEC 60304: Fiber 1-12: Red, green, blue, yellow, white, grey, brown, violet, turquoise, black, orange, pink. Fiber 13-24: Red, green, blue, yellow, white, grey, brown, violet, turquoise, transparent, orange, pinke, each with black ring marking, except transparent.
Tube	Stranded filled loose tube
Strain relief (over all)	Non metallic, glass rovings
Outer sheath material	Halogen free flame retardant compound, UV resistant
Outer sheath (colour)	Black

GigaLine[®] U-DQ(ZN)BH - B2ca

universal cable, stranded loose tube

E9/125 OS2

Mechanical characteristics (cable)

Bending radius (static)	15x outer diameter
Bending radius (dynamic)	20x outer diameter
Crush resistance (short term)	5000 (N/100mm)
Max. strain relief	5000 N

Thermal characteristics (cable)

Temperature (transport / storage)	-40 °C up to +80 °C
Temperature during installation	-5 °C up to +60 °C
Temperature after installation	-40 °C up to +80 °C

Standards, certificates and approvals

Fibre standard	OS2 ITU-T 652.D + G657.A1 IEC 60793-2 B1.3
Cabling standard	EN 50173 ISO/IEC 11801
Fire class	B2ca s1a d1 a1 acc. to EN 50575 / 50399
DoP	CDESK0000092
Flame retardancy	IEC 60332-1-2, IEC 60332-3-22 Cat. A
Halogen free	IEC 60754-1
Smoke density	IEC 61034
Cable standard	IEC 60794-2, IEC 60794-3
Compliance	to CPR (EU/305/2011)

Part number	Number of fibres	Weight	Fire load	Outer diameter
LKD8UC3BK110000	8 x 12	182,0 kg/km	2,8 MJ/m	13,1 mm