

EE2M12N Minicables ADSS - KP Sheath

MICRO ADSS FIBRE-OPTIC CABLES

DESCRIPTION AND APPLICATION

Fibre-optic ADSS cable with dielectric reinforcement elements and high density polyethylene sheath. This cable is designed for aerial self-supported installations in poles along with overhead, telecommunication or high voltage transmission lines.

These cables are used for medium or long distance telecommunications networks and can be designed with single mode type ITU-T G 652D or G657 A1. The cables up to 192 fibres will contain 200 µm G657A1 fibres

CONSTRUCTION

- Central element: Fibre-glass reinforced plastic rod.
- Loose Tubes: PBT loose tubes filled with thixotropic compound. Optional fillers depending on the cable structure. Colour coding according to tables 1 and 2.
- Core formation: Tubes are stranded in SZ.
- Core wrapping: Water-blocking tape and/or yarns to avoid water propagation.
- Outer sheath: Grey HDPE (RAL 7001), UV resistant outer jacket.
- Sheath marking:
Manufacturer – CAVO OTTICO - Number of fibres (YY) FO - OPEN FIBER – (Month-Year) – Identification number of the fibre - Length markers

LOOSE TUBE AND OPTICAL FIBRE COLOUR CODE

Fibre/Tube Colour	1	2	3	4	5	6	7	8	9	10	11	12
	Red	Green	Yellow	Brown	Blue	Violet	Grey	Orange	Rose	White	Black	Turquoise

*Fibers from 13 to 24 will be marked with one black ring each 50 mm.

*Fibers from 25 to 36 will be marked with two black rings each 50 mm.

* In case of the black fiber, this could be natural fiber with one or two black rings.



PRODUCT INFORMATION

CABLE FIBRES	24	48	96	144	192	288	396
Nominal OD (mm)	10.5	10.5	12.5	12.5	12.5	14.1	15.9
Nominal weight (kg/km)	85	85	124	124	129	160	206
Tubes Num.	2	4	4	6	8	8	11
Passive Elements Num.	4	2	2	0	0	0	0
Fibres Number per Tube	12	12	24	24	24	36	36
MAX. TENSILE STRENGTH IN INSTALLATION (MAT) (N) UNE-EN 60794-1-2, Met. E1 $\Delta\epsilon_f \leq 0,25\%$, $\Delta\alpha \leq 0,1$ dB/km after test	6000						
MAX. TENSILE STRENGTH IN OPERATION (MOT) (N) UNE-EN 60794-1-2, Met. E1 $\Delta\epsilon_f \leq 0,05\%$, $\Delta\alpha \leq 0,1$ dB/km after test	3000						
IMPACT RESISTANCE UNE-EN 60794-1-2, Met. E4	5 J, 300 mm ; $\Delta\alpha$ reversible ($\Delta\alpha \leq 0,1$ dB/km after test)						
CRUSH RESISTANCE (N/cm) UNE-EN 60794-1-2, Met. E3	1500 ; $\Delta\alpha$ reversible ($\Delta\alpha \leq 0,1$ dB/km after test)						
REPEATED BENDING UNE-EN 60794-1-2, Met. E6	25 Cycles: 20 x Ø cable, $\Delta\alpha$ reversible ($\Delta\alpha \leq 0,1$ dB/km after test)						
TORSION UNE-EN 60794-1-2, Met. E7	2m cable ; 100N ; 5 cycles ; $\pm 180^\circ$; $\Delta\alpha$ reversible ($\Delta\alpha \leq 0,1$ dB/km after test)						
BENDING UNE-EN 60794-1-2, Met. 11	R=20XØ; 4 turns; 3 cycles, $\Delta\alpha$ reversible ($\Delta\alpha \leq 0,1$ dB/km after test)						
TEMPERATURE CYCLING UNE-EN 60794-1-2, Met. F1	-30°C / 60°C; $\Delta\alpha < 0.05$ dB/km						
WATER PENETRATION UNE-EN 60794-1-2, Met. F5B	LP _{water} ≤ 3 m (24 hours); No leakage						
UV RESISTANCE ISO 4892-2 2013	720 hours, no change in physical-mechanical proprieties						

Optical fibre characteristics: See Annexes – Optical fibre characteristics.

All drawings, weights and dimensions details, as well as tube and fibre colours in this document are only indicative and must not be considered contractual.

Cables de Comunicaciones Zaragoza, SL.

Polígono de Malpica, calle D, nº 83. 50016 Zaragoza – SPAIN

+34 976 729 900 | +34 976 729 974

www.cablescom.com | comercial@cablescom.com

Certified Company ISO 9001 – ISO 14001